PARKWOOD STC DISCLAIMER

Parkwood provide STC values on key doors, for evaluating the acoustic performance of that door. The primary purpose of these values is for comparing products in Parkwood's own range, and with other suppliers of door leaves only.

All STC values are provided based on a nominal 1980 x 860 door size. They have been laboratory tested by the University of Auckland, and *only reflect the value of the door leaf itself.* They do not provide any indication as to the acoustic performance of the frame and seals used.

It is the responsibility of the installer or fabricator to provide a door in frame STC value for the end user.

Door Style	Code	STC (db)	Kg m ⁻²	Rw (db)
Duramax FLW	FLW	24	14	27
Duramax FTS	FTS	24	10	26
Strata TGV	ALSTTGV	24	16	24
Duramax FVW	FVW	25	14	28
Duramax FLS	FLS	26	21	31
Rosewood AR44	EAR44	28	17	27
Duramax AR10S	AR10S	28	21	30
Strata FL	ASFLOO	28	15	28
Thermtek FL	ATFLOO	29	18	29
American White Ash AR44	EAR44	30	19	30
Thermtek FLTGV	ATVVOO	30	20	31
Vulcan TGV	E1	31	17	31
Cedar E1 51mm	E152	31	17	30
Thermtek FLVP10	ATFL10	32	22	32
Thermtek FLAC	AMFL00	33	25	32

*All doors tested at 1980 x 860mm. Values reflect the door leaf only and provide no indication of performance of seals or frame. Altering door sizes, as well as adding vee-grooves and vision panels may affect acoustic performance. It is the responsibility of the installer or fabricator to provide a STC value of the installed door and frame.

P\RKWOOD WELCOME HOME NEW ZEALAND I 0800 10 10 28 sales@parkwooddoors.co.nz parkwooddoors.co.nz

AUSTRALIA I 1800 681 586 sales@parkwooddoors.com.au parkwooddoors.com.au