

# PARKWOOD PIVOT MANUAL

	Therm FL 50mm	Therm FL 41mm	Strata FL 41mm	Duramax 40mm	Duramax 50mm +	Timber 40m	Timber 50mm +	Grandor
<i>Briton 2800 FS</i>	110	N/A	N/A	N/A	70	70 FR	70	N/A
<i>Briton 2800 Transom Closer</i>	140	N/A	N/A	N/A	140	70 FR	140	N/A
<i>Lockwood 985 Transom Closer</i>	140	N/A	N/A	N/A	140	70 FR	140	N/A
<i>Lockwood 985 FS</i>	110	N/A	N/A	N/A	70	70 FR	70	N/A
<i>Ryobi 30 Series Transom Closer</i>	140	N/A	N/A	N/A	N/A	N/A	N/A	N/A
<i>Fritzjurgens M+ Standard</i>	140	N/A	N/A	N/A	N/A	N/A	70	150
<i>Fritzjurgens M+ Cable Grommet</i>	160	N/A	N/A	N/A	N/A	N/A	N/A	170
<i>Panidis Pivot</i>	140*	N/A	N/A	N/A	70*	70 FR*	70*	150*

## KEY:

Numbers show the minimum pivot point from the edge of the door. Values are in millimetres.

FR – Exclude timber doors without a flush rail. Parkwood cannot machine for this pivot in a E1, E1WR door or in AR, VV (Batten) styles.

### \* Important Panidis Pivot Information:

Check the 'Panidis Pivot Mounting' document before specifying this pivot in a timber frame.

## PIVOT INFORMATION

### Briton Pivots

Light-duty bottom pivot only. Heavy duty not available.

Max door weight 80kg

Max door width 1100mm + pivot back set

Adjustable under-door clearance

### Lockwood Pivots

Light-duty bottom pivot only. Heavy duty not available.

Max door weight 110kg

Max door width 1220mm

Adjustable under-door clearance

### Ryobi Pivots

30 Series side load models only

End load models not available

Maximum door width 1050mm

Adjustable under door clearance

### Fritzjurgens M+

High end pivot with integrated closer.

Hold open at 90 degrees.

Under-door clearance fixed at 11mm

Available with cable grommet top pivot

### Panidis Pivot

High end pivot

Free-swing only

Under-door clearance fixed at 13mm